

Specifications

Technical specifications

Technology	Surface Light Wave (upgraded Infrared)
Outside Size	105inch (2327.08±2.0mm*1279.98±2.0mm)
Active Size	102inch (1589.42±2.0mm*1231.00±2.0mm)
Projection Size	98inch (2171.90±2.0mm*1221.00±2.0mm)
Exteral Frame Material	Aluminum frame
Board Surface	Ceramic surface
Aspect Ratio	16:10
Function Hotkey	Hotkey Available
Support OS	Win XP/Win7/Win8/Win10, Vista, Android System, Linux, Mac OS
Driver Mode	Plug and play(HID), usb interface
Power Supply	USB power supply
Voltage	±5V
Current	≤300ma
Touch Points	6TOUCH(optional)
Resolution(Interpolation)	32767*32767
Touch Refresh Rate	≥120FPS (frames per second)
Interference	No static interference no drift phenomenon anti stornq light anti-dust
Touch Physical Resolution	30DPI
Response Speed	<8ms
Minimum Touch Object	3mm*3mm
Power Consumption	≤1.5W
Installation	Wall-mounted or portable floor stand (optional)
Writing Tools	pen, finger, pointer and any other opaque objects
Temperature	Operating: -10°C ~ 50°C Storage: -20°C ~ 60°C
Relative Humidity	Up to 90% RH from 0°C to +40°C, non-condensing
Software	Cloudboard and Airlink(optional)
Lifetime	7 Years

Accessories

Standard Accessory (Free With Boards)	USB cable 5M, stylus pen, board eraser, users manual,warranty card, brackets, presentation stick
--	---

Certification

CE FCC RoHs ISO9001-14000