

SC SERIES INTERACTIVE FLAT PANEL

| Model No. | | SC-65CX | SC-75CX | SC-86CX |
|------------------------|-------------------------------|---|-----------------------|----------------------|
| LED Parameters | Size | 65INCH | 75INCH | 86INCH |
| Screen Type | BACK LIGHT | D-LED | D-LED | D-LED |
| Display Parameters | Active Display Area | 1429 (H) x 804 (V) | 1652.5 (H) x 930.5(V) | 1897 (H) x 1068 (V) |
| | Display frequency | 60HZ | 60HZ | 60HZ |
| | Display Colors | 10bit(D), 1.07Billion colors | | |
| | Resolution | UHD 4K (3840 ×2160) | | |
| | Brightness | 400cd/m2 | 400cd/m2 | 400cd/m2 |
| | Contrast Ratio | 1200: 1 | 1200: 1 | 1200: 1 |
| | Response time | 8ms (typ.) | 8ms (typ.) | 8ms (typ.) |
| | Aspect Ratio | 16:9 | 16:9 | 16:9 |
| | Scren Protecctor | 4mm Tempered Glass with Anti-Glare coating Mohs hardness level 7 | | |
| | Led Life time | 50000Hours | 50000Hours | 50000Hours |
| | Viewing Angle | 178 degrees in horizontal,178 degrees in vertical | | |
| Speaker | Sound Output-Speaker | 8Ω & 15W * 2 | 8Ω & 15W * 2 | 8Ω & 15W * 2 |
| Power Parameters | Power(No PC) | < =280W | < =320W | < =380W |
| | Working Voltage | 100V~240V AC 50 / 60Hz | | |
| | Power Type | AC power | | |
| | Standby Power | ≤ 0.5W | | |
| ANDROID OS | Android System | Android 9.0 4GBRAM + 32GB EMMC | | |
| | CPU /GPU | CPU :Quad-Core A55 1.9GHz, GPU:Mali-G31 MP2 | | |
| | WIFI | WIFI 802.11/a/b/g /n/ac 2.4Ghz & 5Ghz (Including hotspot) | | |
| | Bluetooth | Support | | |
| Input & Output | Input (Backside) | HDMI IN * 2; USB 2.0 * 2 ; USB 3.0*1; Touch USB type-B * 1 ;YPBPR IN*1 ; VGA IN * 1 ; Audio IN * 1 ; RS232 UART IN * 1 , RJ45 (IN) 10/100MB *1 ; AV IN *1 ; DP IN *1; RF*1; SD *1; OPS JACK *1 ; | | |
| | OutPut (Backside) | EARPHONE OUT*1; COAX OUT*1 | | |
| | Front Connection | HDMI IN *1 (front), Touch USB *1 (front), USB 3.0* 3 (Front) | | |
| Touch parameters | Touch Technology | Infrared technology (IR) | | |
| | Touch Points | 20TOUCH (Windows) 16TOUCH(Andoid) | | |
| | Inductive objects | Finger or pen or any Opaque Object | | |
| | Acuracy | Φ 2mm | | |
| | Resolution | 32767*32767 | | |
| | Response time | ≤6ms (150FPS) | | |
| | Report number | 150frames per second For single touch | | |
| | Working life | >60000 hours | | |
| | Anti-Light | ≥80000lux | | |
| | Operation System | HID Support & Support Windows , Mac, Android , Linux | | |
| Standard configuration | Accessories | Remote control* 1; Power cable *1 ; Pointer*1, Quick start guide ; Stylus Pen *2 ; User Manual *1 ; Wall bracket *1 ; | | |
| Features | | Support WIFI 802.11/b/g/n /ac & Lan Network 10/100MB; Wireless Projection& Sharing ; Smart Whiteboard Software & Annotation Function; Screen Recoder; Smart Tools | | |
| Packing Parameters | physic Size | 1485×901.6×91.8mm | 1707.4×1026.8×91.8mm | 1953.6×1165.6×91.8mm |
| | Plywood Carton Size | 1694×227×1067mm | 1860×280×1145mm | 2160 x280×1340mm |
| | Net Weight | 41kg | 55kg | 67.1kg |
| | Gross Weight | 58g | 69.5kg | 86.4kg |
| Enviroment | Storage & Working Temperature | -10 ℃~ 55 ℃ | -10 ℃~ 55 ℃ | -10 ℃~ 55 ℃ |
| | Storage &Working Humidity | 10% ~90% humidity | 10% ~90% humidity | 10% ~90% humidity |
| | Max Working Time | 16hrs *7 Days | | |
| OPS PC (Optional) | | Proecessor INTEL®CORE I5; RAM with 4GB ; Storage SSD 128GB (OPTIONAL OR CUSTOMIZED) | | |