

CLEVERMAX

SE SERIES INTERACTIVE FLAT PANEL SPEC

Model No.		SE-65CX	SE-75CX	SE-86CX
LED Parameters	Size	65INCH	75INCH	86INCH
	BACK LIGHT	D-LED	D-LED	D-LED
Display Parameters	Active Display Area	1428.48 (H) x 803.52 (V)	1649.67 (H) x 927.94(V)	1895.04 (H) x 1065.96 (V)
	Resolution	3840 ×2160 @60HZ	3840 ×2160 @60HZ	3840 ×2160 @60HZ
	Contrast Ratio	1200 1	1200 1	1200: 1
	Brightness	400cd/m2	400cd/m2	400cd/m2
	Display Colors	1.07 B	1.07 B	1.07 B
	Aspect Ratio	16:9	16:9	16:9
	Response time	8ms (typ.)	8ms (typ.)	8ms (typ.)
	Viewing Angle	178°	178°	178°
	Led Life time	50000 Hours	50000 Hours	50000 Hours
	Bonding Technology	Zero Bonding	Zero Bonding	Zero Bonding
	Screen Protecctor	3mm Tempered AG Glass	3mm Tempered AG Glass	3mm Tempered AG Glass
Speaker	Sound Output-Speaker	2*15W	2*15W	2*15W
Power Parameters	Power(No PC)	≤250W	≤350W	≤ 550W
	Working Voltage	100-240V~ 50/60Hz 4A	100-240V~ 50/60Hz 4A	100-240V~ 50/60Hz 4A
	Standby Power	≤ 0.5W	≤ 0.5W	≤ 0.5W
ANDROID OS	Android System	Android 11 4GBRAM + 32GB EMMC (Standard)		
	CPU /GPU	Quad Core A55 2.0GHz, Mali G52MP2		
	WIFI	WIFI 802.11/a/b/g /n/ax (2.4Ghz + 5Ghz) WIFI6 with Hotspot 5Ghz		
	Bluetooth	Bluetooth 5.0		
	UI Resolution	4K		
	Ethernet network	10M/100M/1000M (Default)		
Input & Output	Input (Backside)	RJ45 IN*1;SPDIF*1;RS232*1;HDMI IN *2;Touch USB*1; Audio IN*1;USB 2.0*1;USB 3.0*2;VGA IN*1		
	OutPut	RJ45 OUT*1; Audio Out*1;HDMI OUT *1;		
	Front Connection	USB 3.0*2 ; HMDI IN*1 ; TOUCH USB *1 ; TYPE C *1		
Touch parameters	Touch Technology	Infrared technology (IR)		
	Touch Points	Windows system: 20TOUCH; Android system: 20 TOUCH		
	Inductive objects	Finger or pen		
	Acuracy	Φ 1mm		
	Response time	≤5ms		
Features	Wireless Projection & Screen Sharing	Support		
	Screen Recorder	Support		
	Smart Whiteboard &Annotation Function	Support		
	Special Functions	Camera, Timer, Calendar, Calculator, Countdown, Split Screen, Screen Capture, Energy Saving, Eye Protection, Floating Menu Toolbar, Vote, Touch Lock, Quick File Transfer, Welcome Page, Cloud Driver, Google Play		
Environment	Storage & Working Temperature	Working Temperature: 0 °C~ 40 °C, Storage Temperature: -20 °C~ 60 °C		
	Storage &Working Humidity	10% ~90%		
Packing Parameters	physic Size	1488.4×896.6×87.2mm	1709×1020×88mm	1957×1160×100mm
	Plywood Carton Size	1630×220×1050mm	1860×220×1160mm	2120×220×1325mm
	Net Weight	35±1 kg	48±1 kg	59±1 kg
	Gross Weight	47±1 kg	62±1 kg	82±1 kg
	Standard configuration	Accessories	Remote control* 1; Power cable 1.5M *1; Quick start guide ; Stylus Pen *2 ; Wall mounted Bracket *1;	